## **ERGONOMIC CASTERS**

INTRODUCING THE NEW

## Poly Flexon WHEEL

Round Tread Polyurethane on Aluminum Core





are designed for superior ergonomic performance. Protect your workers from injury! An improper wheel under a heavy load pushed or pulled poses significant injury risk. The resilient 85 Shore A polyurethane makes this wheel glide quietly across even the most debris covered floors, while maintaining the durability to carry loads up to 1500 lbs per wheel.

The wheel treads are chemically and mechanically molded onto a lightweight aluminum core. The PolyFlexon wheels are provided with 2 pieces of a 6203RS precision bearing with top hat spacers for ½" bore.

- Ergonomic rounded tread with precision bearings allows for easier maneuvering and reduces your pushing and pulling efforts
- · Designed to roll easily and quietly
- · Capacity up to 1500 pounds per wheel
- · Deflects debris
- · Rounded tread design provides for easier swiveling
- · Non-marking



## Durometer: 85 Shore A

Part Number	Туре	Wheel Diamter	Tread Width	Load Cap	Overall Height
53736	rigid	4"	2"	800 lbs	5-5/8"
53734	swivel	4"	2"	800 lbs	5-5/8"
53735	swivel with brake	4"	2"	800 lbs	5-5/8"
53739	rigid	5"	2"	1000 lbs	6-1/2"
53737	swivel	5"	2"	1000 lbs	6-1/2"
53738	swivel with brake	5"	2"	1000 lbs	6-1/2"
53742	rigid	6"	2"	1250 lbs	7-1/2"
53740	swivel	6"	2"	1250 lbs	7-1/2"
53741	swivel with brake	6"	2"	1250 lbs	7-1/2"
53745	rigid	8"	2"	1500 lbs	9-1/2"
53743	swivel	8"	2"	1500 lbs	9-1/2"
53744	swivel with brake	8"	2"	1500 lbs	9-1/2"







## PolyFlexon



1450 Radisson St Green Bay, WI 54302
P 920.432.2928 | TF 800.472.2118 | F 920.432.8065
sales@thecasterguy.com | thecasterguy.com