



INTRODUCING THE NEW **AN & AX WHEELS**

Round Tread Polyurethane on Aluminum Core



How can we help?

New maintenance free AX & UX wheels

are designed for superior ergonomic performance. Protect your workers from injury! An improper wheel under a heavy load pushed or pulled poses significant injury risk. The resilient 85 Shore A polyurethane makes this wheel glide quietly across even the most debris covered floors, while maintaining the durability to carry loads up to 1500 lbs per wheel.

The wheel treads are chemically and mechanically molded onto a lightweight aluminum core. The AX and UX wheels are provided with 2 pieces of a 6203RS precision bearing with top hat spacers for 1/2" bore.

- Designed to roll easily and quietly
- Capacity up to 1500 pounds per wheel
- Deflects debris
- Rounded tread design provides for easier swiveling
- Non-marking
- Ergonomic rounded tread with precision bearings allows for easier maneuvering and reduces your pushing

WWW.ONEMONROE.COM



+1 855-771-4199



sales@askmonroe.com



www.onemonroe.com

AN

DUROMETER: 80-85 SHORE A



Top Plate AN Wheel	Type	Wheel Diameter	Tread Width	Load Cap	Overall Height
110AN04228R	Rigid	4"	2"	800 lbs	5-5/8"
110AN04228S	Swivel	4"	2"	800 lbs	5-5/8"
110AN04228SFBE	Swivel with brake	4"	2"	800 lbs	5-5/8"
110AN05228R	Rigid	5"	2"	1000 lbs	6-1/2"
110AN05228S	Swivel	5"	2"	1000 lbs	6-1/2"
110AN05228SFBE	Swivel with brake	5"	2"	1000 lbs	6-1/2"
110AN06228R	Rigid	6"	2"	1250 lbs	7-1/2"
110AN06228S	Swivel	6"	2"	1250 lbs	7-1/2"
110AN06228SFBE	Swivel with brake	6"	2"	1250 lbs	7-1/2"
110AN08228R	Rigid	8"	2"	1500 lbs	9-1/2"
110AN08228S	Swivel	8"	2"	1500 lbs	9-1/2"
110AN08228SFBE	Swivel with brake	8"	2"	1500 lbs	9-1/2"

AX

DUROMETER: 85 SHORE A



Top Plate AX Wheel	Type	Wheel Diameter	Tread Width	Load Cap	Overall Height
GAR04X2R-AX	Rigid	4"	2"	800 lbs	5-5/8"
GAR04X2S-AX	Swivel	4"	2"	800 lbs	5-5/8"
GAR04X2S-AX-B	Swivel with brake	4"	2"	800 lbs	5-5/8"
GAR05X2R-AX	Rigid	5"	2"	1000 lbs	6-1/2"
GAR05X2S-AX	Swivel	5"	2"	1000 lbs	6-1/2"
GAR05X2S-AX-B	Swivel with brake	5"	2"	1000 lbs	6-1/2"
GAR06X2R-AX	Rigid	6"	2"	1250 lbs	7-1/2"
GAR06X2S-AX	Swivel	6"	2"	1250 lbs	7-1/2"
GAR06X2S-AX-B	Swivel with brake	6"	2"	1250 lbs	7-1/2"
GAR08X2R-AX	Rigid	8"	2"	1500 lbs	9-1/2"
GAR08X2S-AX	Swivel	8"	2"	1500 lbs	9-1/2"
GAR08X2S-AX-B	Swivel with brake	8"	2"	1500 lbs	9-1/2"



+1 855-771-4199



sales@askmonroe.com



www.onemonroe.com



ONE MONROE