



REVISIONS:

DATE	#	COMMENT	BY

PART NO: 14437

DIMENSIONS AND TOLERANCE ARE IN INCHES UNLESS SPECIFIED:
 .X ±0.1 .XX ±0.06 .XXX ±0.03 FRACTION ±1/16 ANGLES ±1°

SPECIFICATIONS:

YOKE:

1. MATERIAL: ZINC PLATED, HOT FORGED ASTM 1045 STEEL
2. PRECISION MACHINED & INDUCTION HARDENED RACEWAYS
3. 3/4" KINGPIN AND NUT
4. GREASE FITTING IN SWIVEL RACEWAY
5. 3/4" AXLE AND LOCK NUT
6. WITH FACE-CONTACT BRAKE AND 4-POSITION LOCK

WHEEL:

1. MATERIAL: POLYURETHANE TREAD ON CAST IRON CORE
2. 95 (±5) SHORE A DUROMETER
3. TEMPERATURE RANGE -40°F TO 180°F
4. 1" I.D. X 1-15/16" O.D. X 3" L. ROLLER BEARING
5. COLOR: GREE TRAEAD ON BLACK CORE

LOAD CAPACITY : 2000 LBS

DATE	09/19/2024
SCALE	
PAGE	1 OF 1
DRAWN BY	D.X.
APPROVED BY	S.C.

